

A 100 / A 200

PROFESSIONAL TWO CHANNEL POWER AMPLIFIERS

These professional power amplifiers boast an ultra-slim body and modern design. They feature screw terminal speaker outputs and balanced Phoenix input connectors. The unit includes a fan cooling system and a bridge mode selector for versatile operation. Designed for live music, background music, and voice, the amplifier provides complete circuit fault protection to ensure reliability. Its high-performance stereo output makes it ideal for the installation market's low-power amplifier needs.



Technical Specifications	A 100	A 200
Output power	Rated 100W + 100W (4 Ω), 70W+70W (8 Ω)	Rated 200W + 200W (4 Ω), 130W+130W (8 Ω)
Power supply	~230 V/115 V 50/60Hz	
Outputs	Screw terminal block	
Inputs	Connectors - Balanced Phoenix, Impedance - 10 k Ω , input sensitivity - 0,775V	
Frequency response	25 Hz - 25 kHz	
THD	< 0,03 %	
Signal / noise ratio	> 100 dB	
Damping factor	> 400 at 8 Ω	
Controls	Power switch, volume, mode selector	
Indicators	Power, signal, clip, protect	
Dimensions	482 mm x 45 mm x 320 mm	
Weight	7,8 kg	9 kg
Mounting	19" rack	
Colour	Black (RAL 9017)	

A 100 / A 200

PROFESSIONAL TWO CHANNEL POWER AMPLIFIERS

Front panel view



Rear panel view

